

*RE - C -360-7.50* PCB Terminal block 7.5mm Pitch

**Electrical :**

Rated voltage: 300V  
 Rated current: 16A  
 Contact resistance: 20m $\Omega$   
 Insulation resistance: 5000M $\Omega$ /1000V  
 Withstanding Voltage: AC15000V/1Min  
 Wire range: 22-14AWG 2.5mm<sup>2</sup>

**Material:**

Screws: M3 steel Zinc plated  
 Wire guard: phosphor bronze Ni plated or stainless steel  
 Pin header: Brass, Tin plated  
 Housing: PBT,UL94V-0

**Mechanical:**

Temp. Range: -30 $^{\circ}$ C~+120 $^{\circ}$ C  
 MAX Soldering: +250 $^{\circ}$ C for 5 Sec.  
 Torque: 0.5Nm (4.5lb.in)  
 Strip length: 4.5-5mm


Product NO.: *RE - C -360-7.50-03P-3S*

Pos. NO. \_\_\_\_\_ S=Slot Screw  
 Series No. \_\_\_\_\_ Color: 2=Blue, 3=Black  
 Pitch 7.50=7.50mm \_\_\_\_\_ Pin Number:02/03 Pin



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm		SHEET SIZE:A4		SCALE: ---	
> 0 ~ 3	> 3 ~ 18	> 18 ~ 50	> 50 ~ 120		
$\pm 0.12$	$\pm 0.15$	$\pm 0.3$	$\pm 0.5$		



TERMINAL BLOCK