



Order Code	Rated Voltage	Operating Voltage	Max. Rated Current	Min. S.P.L. (@60cm)	Resonant Frequency	Tone Nature	Operating Temp	Weight
RE-B-PB-43*33A-A1	12V <sub>DC</sub>	6-28V <sub>DC</sub>	20mA	80dB	2.9 ± 0.5KHz	Continuous	-20~+80°C	40g
RE-B-PB-43*33A-A2	12V <sub>DC</sub>	6-28V <sub>DC</sub>	20mA	80dB	2.9 ± 0.5KHz	Slow Pulse		
RE-B-PB-43*33A-A3	12V <sub>DC</sub>	6-28V <sub>DC</sub>	20mA	80dB	2.9 ± 0.5KHz	Fast Pulse		
RE-B-PB-43*33A-A4	12V <sub>DC</sub>	6-28V <sub>DC</sub>	20mA	80dB	2.9 ± 0.5KHz	Slow Pulse		
RE-B-PB-43*33A-A5	12V <sub>DC</sub>	6-28V <sub>DC</sub>	20mA	80dB	2.9 ± 0.5KHz	Fast Pulse		
RE-B-PB-43*33A-B1	230V <sub>AC</sub>	200~ 240V <sub>AC</sub>		80dB	2.9 ± 0.5KHz	Continuous		
RE-B-PB-43*33A-B2	230V <sub>AC</sub>	200~ 240V <sub>AC</sub>		80dB	2.9 ± 0.5KHz	Fast Pulse		
RE-B-PB-43*33A-B3	230V <sub>AC</sub>	200~ 240V <sub>AC</sub>		80dB	2.9 ± 0.5KHz	Slow Pulse		

### PiezoBuzzerSeries

RE-B-PB-43\*33A With Circuit Piezo Buzzer Series

#### SPECIFICATION

Rated Voltage: 12V<sub>DC</sub>  
 Operating Voltage: 6-28V<sub>DC</sub>  
 Max. Rated Current: 20mA at 12V<sub>DC</sub>  
 Min. S.P.L. (@60cm): 80dB at 12V<sub>DC</sub>  
 Resonant Frequency: 2.9 ± 0.5KHz  
 Tone Nature: Continuous  
 Operating Temp: -20~+80°C  
 Weight: 40g

#### ORDER INFORMATION

Product NO.: RE-B- PB - 43\*33A-A1

Part Number \_\_\_\_\_ Order Code \_\_\_\_\_  
 Piezo Buzzer Series