



Note:

- 1: V.S.W.R: 1.5(0~3G), Max.
- 2: Wire surface shall have no dirt, broken.
- 3: Connector surface with coating, oxidation phenomenon.
- 4: Connector pins and insulator are in the same plane

Order Information

RE - ANT - RFCA06 - OD1.13 - L300 / X

- Wire Color: Not - Black
G-Gray BR-Brown
- Lengs: L300=300mm
- Cable: OD0.81- 0.81mm RF Cable
- OD1.13- 1.13mm RF Cable
- OD1.32- 1.32mm RF Cable
- OD1.37- 1.37mm RF Cable
- RG178- RG178 RF Cable
- RG316- RG316 RF Cable
- Series: I-PEX to RP SMA Jack, Female
- RoHS

No.	Name	Description	UNITS	Q'ty
7	CAP	Rubber CAP,Red	PCS	1
6	Nut	T1.8mm Nut, 1/4 36UNS-2A	PCS	1
5	Washers	T0.4mm Washers	PCS	1
4	Connector	RP SMA Jack, Female Straight, for RG178, RG316, 0.81, 1.13, 1.32, 1.37mm	PCS	1
3	RF Cable	RG178, RG316, 0.81, 1.13, 1.32, 1.37mm Cable	mm	L
2	Heat-Shrink Tube	∅1.0mm Heat-Shrink Tube, Block, L15mm	PCS	2
1	Connector	I-PEX Plug, for RG178, RG316, 0.81, 1.13, 1.32, 1.37mm Cable	PCS	1

UNITS:mm		SHEET SIZE:A4		SCALE: ---		First angle projection
> 0 ~ 3	> 3 ~ 18	> 18 ~ 50	> 50 ~ 120			
± 0.12	± 0.15	± 0.3	± 0.5			