

Specifications

Contact Rating: 25 mA At 24VDC(Switching)
 100 mA At 50VDC(Steady State)
 Life: 2,000 Cycles
 Contact Resistance: 100mΩ Max.
 Insulation: 100MΩ at 100VDC Min
 Dielectric Strength: 300VAC Min
 Storage Temperature: -20°C~75°C
 Operating Temperature: -40°C to 85°C.
 Operation Force : 8N Max.
 Resistance To Solder: 240 5°C At 5s

Materials


Base & Cover: PPS (UL94V-0)
 Actuator: PA46 (UL94V-0).
 Contacts: Brass, Gold/Tin Plate
 Terminals: Brass, Gold/Tin Plate

ORDER INFORMATION

RHTGYP-XX-N-0 0
 2.54mm Piano Type Dip Switch
 Number of Pos.:02,04,06,08Pos.
 Color: N=Black
 0:Without Sealed
 Packaging: 0=Tube

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

2.54mm Piano Type DIP Switch
 THIRD ANGLE PROJECTION

 RHTGYP