



Material:
 Insulator:High Temperature Thermoplastic,UL 94 V-0.
 Contact:Copper Alloy
 Shell:Stainless.
 Plating:
 Contact:Plated Ni,contact point gold plated 15u" Au min,welding feet matte tin.
 Shell:Plated Ni overall Plated G/F Selective contact area.
 CD Pini:Plated Ni, tin feet,contact point brush gold.
 Electrical:
 Current Rating:0.5A.
 Voltage Rating:125V AC/DC
 Ambient Temperature Range:-20℃~+60℃
 Storage Temperature Range:-40℃ +70℃
 Ambient Humidity Range:95% R.H. Max.
 Contact Resistance:100mΩ Max.
 Insulation Resistance:1000MΩ Min./500V DC
 Mating Cycles:5000 Insertions.
 Temperature:260℃

Pin No.	Description
P1#	C1:VCC
P2#	C5:GND
P3#	C2:RST
P4#	C6:VPP
P5#	C3:CLK
P6#	C7:I/O

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm SHEET SIZE: A4 SCALE:---

0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5

DRWN BY PAN
 CHK'D BY FENG
 APPR BY ZHAN

SIM CARD CONN;PUSH PUSH,6P,H1.85mm,SMD
 THIRD ANGLE PROJECTION
 RHTAYIM-030E-6P-R