

Dimension

Position	A	B
28	40.5	23.12
32	44.1	26.6
42	52.8	35.9
56	65.4	48
64	72.3	55.1

Materials:

Contact: Copper Alloy.

Insulator: Thermoplastic

1. ELECTRICAL Specifications:

Contact Rating: 50V DC, 100mA.

Contact Resistance: 50mΩ max.

Insulation Resistance: 1000M Min.

Dielectric strength: 500V DC min.
for 60 seconds.

2. MECHANICAL AND ENVIRONMENTAL

Operating Temperature: -40°C~+105°C

Storage Temperature: -20°C~+70°C

Operating Life: 25,000 cycles

Humidity: 95%RH, 40°C for 96 Hrs.

Vibration: Per MIL-STD-202F, METHOD 201A

Solderability: After flux 230°C for 5
0.5 Seconds, 95% coverage

Soldering Heat: 260 ±5°C for 5 ±1 Seconds

ORDER INFORMATION

Product No.: RHTAY08Y-XX

SHRINK DIP SOCKET 1.778mm Series

Number of Contacts: XX=28-64Pin



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

ZIF SOCKET PITCH 1.778mm ROHS

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12


±0.15

±0.3

±0.5

APPR BY ZHAN

THIRD ANGLE PROJECTION



RHTAY08Y