


Material  
Housing: High Temperature Thermoplastic,  
UL94V-0 PBT, Black/White.  
Contact: Copper Alloy C2680  
Shell: Copper Alloy C2680/SPCC

Finish:  
Contact: Plated Gold In Mating Area; Tin On Solder Tails  
Shell: Nickel Plating

Electrical:  
Current Rating: 1.5A/Contact Terminal.  
Voltage Rating: 30V DC  
Contact Resistance: 30mΩ Max.  
Dielectric Withstanding Voltage: 500 V AC AT Sea Level.  
Insulation Resistance: 1000MΩ Min.  
Connector Mate And Unmated Force  
Mate Force: 3.75kgf Max.  
Unmated Force: 1.02kgf Min.  
Terminal Retention: 1.2kgf Min

Order Information

RHTAY822-B  
CONN USB 2.0  
Color: W=White B=Black



**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE: ---	
0~3	3~18	18~50	50~120	
±0.12	±0.15	±0.3	±0.5	

DRWN BY PAN  
CHK'D BY FENG  
APPR BY ZHAN

CONN COM TYPE A USB Female R/A  
THIRD ANGLE PROJECTION  
 RHTAY822-X