






SECTION A-A



RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05mm

Material
Housing: High Temperature Thermoplastic,
UL94V-0 PBT, Black/White.
Contact: Copper Alloy C2680
Shell: Copper Alloy C2680/SPCC

Finish:
Contact: Plated Gold In Mating Area; Tin On Solder Tails
Shell: Nickel Plating

Electrical:
Current Rating: 1.5A/Contact Terminal.
Voltage Rating: 30V DC
Contact Resistance: 30mΩ Max.
Dielectric Withstanding Voltage: 500 V AC AT Sea Level.
Insulation Resistance: 1000MΩ Min.
Connector Mate And Unmated Force
Mate Force: 3.75kgf Max.
Unmated Force: 1.02kgf Min.
Terminal Retention: 1.2kgf Min

Order Information

RHTAY807-B

CONN USB 2.0

Color: W=White B=Black



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

CONN COM TYPE A USB Female R/A,L10.0

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTAY807-X