







PC Board Layout



#### Material:

Housing: PBT+Glass Filled Polyester  
Flammability Rating: UL94V-0  
Contacts: Phosphor Bronze Ø0.46mm  
Plating: Gold Plating

#### Electrical:

Voltage Rating: 125VAC  
Current Rating: 1.5A  
Contact Resistance: 30mΩ Max.  
Insulation Resistance: 500MΩ Min.  
Dielectric Strength: 1000VAC Rms 50Hz, 1 Min.  
Durability: 600 cycles Min.  
Operation Temperature: -40℃~+70℃

#### Order Information

RHTLY40-8P8C-W/□-1-XX

Contacts: 8P8C

Color Code: 1-Black

Plating Code:

01-Fu" Gold Plating

02-3u" Gold Plating

03-6u" Gold Plating

04-15u" Gold Plating

05-30u" Gold Plating

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

RJ45-8P8C Modular jacks

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTLY40-8P8C-W/□-1-XX