



1 2 3 4 5 6 7 8 9

A



PCB Layout



Material:

Housing:PBT+Glass Filled Polyester

Flammability Rating:UL94V-0

Contacts:Phosphor Bronze Ø0.46mm

Plating:Gold Plating

Electrical:

Voltage Rating:125VAC

Current Rating:1.5A

Contact Resistance:30mΩ Max.

Insulation Resistance: 500MΩ Min.

Dielectric Strength:1000VAC Rms 50Hz,1 Min.

Durability:600 cycles Min.

Operation Temperature:-40°C~+70°C

Order Information

RHTLY51-8P8C-1-XX

Contacts:8P8C

Color Code:1-Black

Plating Code:



01-Fu" Gold Plating

02-3u" Gold Plating

03-6u" Gold Plating

04-15u" Gold Plating

05-30u" Gold Plating



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

Modular jacks RJ45-8P8C 1x1 without Shield



RHTLY51-8P8C-1-XX

1 2 3 4 5 6 7 8 9