







PCB Layout



Material:

Housing: PBT+Glass Filled Polyester

Flammability Rating: UL94V-0

Contacts: Phosphor Bronze $\phi 0.46\text{mm}$

Plating: Gold Plating

Shield: Brass, Tin Plating

Electrical:

Voltage Rating: 125VAC

Current Rating: 1.5A

Contact Resistance: $30\text{m}\Omega$ Max.

Insulation Resistance: $500\text{M}\Omega$ Min.

Dielectric Strength: 1000VAC Rms 50Hz, 1 Min.

Durability: 600 cycles Min.

Operation Temperature: -40°C ~ $+70^{\circ}\text{C}$

Order Information

RHTLY13-8P8C-2x4-X-G/Y-XX

Contacts: 8P8C

Shield Code:

1-with Shield

2-with EMI Shield

LED Code: LEFT/RIGHT

G/Y-Green/Yellow

Y/G-Yellow/Green

Plating Code:

01-Fu" Gold Plating, 02-3u" Gold Plating

03-6u" Gold Plating, 04-15u" Gold Plating

05-30u" Gold Plating

RHTECP® NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15


±0.3

±0.5

APPR BY ZHAN

Modular jacks RJ45-8P8C
2x4 Jack Shield with LED

THIRD ANGLE PROJECTION



RHTLY13-8P8C-2x4-X-X/X-XX