



1 2 3 4 5 6 7 8 9

A



Without shrapnel



With shrapnel

MATERIAL

Insulator: PBT+Glass Fiber,UL94v-0

Contact: Phosphor Bronze

Shell: Spcc, Tin plated

Specification

Current rating: 1 A Max.

Dielectric withstanding voltage: 750 V (AC) for 1 min.

Contact resistance: 30 mΩ Max.

Insulation resistance: 1000 MΩ Min.

Temperature range: -40°C~+105°C

Finishes

contacts: Gold flashed 1u", 3u", 5u", 10u", 15u", 30u".

Shell: Nickel, tin or gold plated

ORDER INFORMATION

MINI DIN Jack Right Angle Double Type

Product NO.: RHTAY55A-44 G/P-0

MINI DIN Jack Right Angle Double Type

Pin Number 44=4/4P 64=6/4P 84=8/4P

46=4/6P 66=6/6P 86=8/6P

48=4/8P 68=6/8P 88=8/8P

Color: G/P=Green+Purple

G/B=Green+Black, B/B=Black+Black

Shrapnel:

0:Without shrapnel

1:With shrapnel

ARRANGEMENT OF CONTACT			
POS. NO.	4PIN/4PIN	6PIN/6PIN	8PIN/8PIN
P.C.B.LAYOUT (BOTTOM VIEW)			

RHTECP® NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

MINI DIN Jack Right Angle Double Type

0~3

3~18

18~50

50~120

CHK'D BY FENG

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN

THIRD ANGLE PROJECTION



RHTAY55A-44G/P-0

1

2

3

4

5

6

7

8

9

A

B

C

D

E

F

G