



PCB LAYOUT  
(Top View)



#### MATERIAL

- 1.Housing Material: Glass Filled Polyester UL94V-0 PBT, NYLON
- 2.Housing Color: Black, Gray, Ivory, White or Others
- 3.Contact Material: Phosphor Bronze  $\varnothing 0.46\text{mm}$
- 4.Plating: Gold plating over nickel. Gold plating thickness 1.5u"/3u"/6u"/15u"/30u"/50u"

#### ELECTRICAL

- 1.Current Rating:1.5Amp
- 2.Voltage Rating:125VAC
- 3.Contact Resistance: 30 M $\Omega$  Max.
- 4.Insulation Resistance: 500 M $\Omega$  Min. @500VDC
- 5.Withstanding Voltage:1000VAC RMS 50Hz 1 minute

#### MECHANICAL

- 1.Durability : 750 cycles Min.
- 2.PCB Retention pre-solder : 1 LB MIN

#### ENVIRONMENTAL

- 1.Storage :-40°C~+80°C
- 2.Operation:-40°C~+70°C

#### ORDER INFORMATION

RHTLY49-4P4C-W-B-XX-X

Part Number	Point NO.	Panel	Part Color	Gold Thickness	Plastic
4P4C	Point	W-With Panel	1-Black	01-Fu"	1-Nylon
4P2C	Point	W/O-Without Panel	2-Gray	02-3u"	2-PBT
			3-White	03-6u"	3-ABS
			4-IV	04-15u"	
				05-30u"	
				06-50u"	

**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

PCB Modular Jack 59 Series

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

RHTLY49-4P4C-W-B-XX-X


±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



1

2

3

4

5

6

7

8

9