



SPECIFICATION
 Rated Load:DC 30V 5A
 Contact Resistance:30mΩ, Max
 Insulation Resistance:100MΩ, Min
 Withstand Voltage:AC500V
 Actuating Force:3-20N
 Life:5000 Cycles
 Operating Temperature:-30°C-70°C

RECOMMENDED PLUG

| NO | Description | QTY | Material | Plating |
|----|--------------|-----|----------|------------|
| 1 | Spring | 1 | Bronze | Sn-Plating |
| 2 | Curve Piece | 1 | Brass | Sn-Plating |
| 3 | Flag Piece | 1 | Brass | Sn-Plating |
| 4 | PIN | 1 | Brass | Ni-Plating |
| 5 | Axis Support | 1 | Brass | Ni-Plating |
| 6 | Housing | 1 | PBT | --- |
| 7 | NUT | 1 | Brass | Ni-Plating |
| 8 | Split Washer | 1 | Iron | Ni-Plating |



| | | |
|------|------|------|
| PIN | ∅2.0 | ∅2.5 |
| APPD | | |



RHTECP NINGBO RHT ELECTRONIC CO.,LTD

| | | | | | |
|----------|----------------|-------|--------|---------------|-------------|
| UNITS:mm | SHEET SIZE: A4 | | | SCALE:--- | DRWN BY PAN |
| 0~3 | 3~18 | 18~50 | 50~120 | CHK'D BY FENG | |
| ±0.12 | ±0.15 | ±0.3 | ±0.5 | APPR BY ZHAN | |

30V 5A DC Jack DIP

THIRD ANGLE PROJECTION

RHTAYD13C-025