

SPECIFICATION


Rated Load:DC 20V 5.5A  
 Contact Resistance:30mΩ, Max  
 Insulation Resistance:100MΩ, Min  
 Withstand Voltage:AC500V  
 Actuating Force:5-30N  
 Life:5000 Cycles  
 Operating Temperature:-30°C~70°C

NO	Description	QTY	Material	Plating
1	Housing	1	PA9T	---
2	Spring Piece	1	Bronze	Ag-Plating
3	Contact Foot	1	Brass	Ag-Plating
4	PIN	1	Zinc Alloy	Ni-Plating
5	Coat	1	Iron	Ni-Plating
6	Spring Piece	1	SUS301	---

PCB LAYOUT TOP VIEW

PIN	Ø2.0	Ø2.5
APPO		

SCHEMATIC



**RHTECP** NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4			SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120	CHK'D BY FENG	
±0.12	±0.15	±0.3	±0.5	APPR BY ZHAN	

20V 5.5A DC Jack Mid Mount 3.65mm  
 THIRD ANGLE PROJECTION  
 RHTAYDC-040