






	1	2	3	4	5	6	7	8	9
A									
B									
C									
D									
E									
F									
G	 NINGBO RHT ELECTRONIC CO.,LTD			UNITS:mm 0~3 3~18 18~50 50~120 ±0.12 ±0.15 ±0.3 ±0.5	SHEET SIZE: A4 SCALE: ---	DRWN BY PAN CHK'D BY FENG APPR BY ZHAN	Metal R/A PCB Mount Dual RCA Jack THIRD ANGLE PROJECTION 		
	1	2	3	4	5	6	7	8	9



PCB HOLE LAYOUT(TOLERANCE:±0.1)
BOTTOM VIEW

Electrical Specification:
Contact resistance:30mΩ Max
Insulation resistance:50MΩ Min at DC 500V
Withstand voltage:AC 500V(50Hz) 1min
Operating Temperature:-25°C~+85°C
Materials:
Plastic : PBT UL94V~0
Sealed Plate : Brass
Terminal : Brass
Outer Contact : Brass
Washer : PBT UL94V~0
Cover : ABS UL94V~0
Housing : PBT UL94V~0

ORDER INFORMATION
Product NO: RHTAYCA-202-N-BK-BK

RCA Jack Type
G:Nickel Plated
Color:BK-BK Black-Black
RE-WH Red-White
WH-RE White-Red
RE-YE Red-Yellow