

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-bottom view)

UNLESS OTHERWISE SPECIFIED,
TOLERANCE ON DECIMAL: ±0.3

Electrical Specification:

Contact resistance : 30mΩ Max

Insulation resistance : 50MΩ Min at DC 500V

Withstand voltage : AC 500V(50Hz) 1min

Operating Temperature : -25°C~+85°C

Materials:

Sealed Plate : Steel

Earth Fitting : Brass

Terminal : Brass

Housing : PBT UL94V~0

Washer : ABS UL94V~0

Outer Contact : Brass

Ground Contact : Brass

Center Contact : Brass

ORDER INFORMATION

Product NO.: RHTAYCA-205-N-R

RCA Jack Type

NiNickel Plated

Color: R:Red ,B:Black

Y:Yellow, W:White,

MODEL NO.	RHTAYCA-205	
	S JACK	PIN JACK
SCHEMATIC		

NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4		SCALE:---
0~3	3~18	18~50	50~120
±0.12	±0.15	±0.3	±0.5


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

PIN Jack+S PCB Mount R/A Jack

THIRD ANGLE PROJECTION



RHTAYCA-205-N-R