



Panel mount



Front view



Back view

Material:
 SHELL Housing: Zinc alloy, Nickel plated
 Insert Housing: PA66+GF 20%
 Contact: Brass, Silver plated
 Termination: Solder
 Locking: Threaded Coupling
 Version: Straight
 Mating life: 500 cycles
 IP rating: IP65
 Cable Diameter: $\phi 6.0 \sim \phi 8.5 \text{mm}$
 Temperature Range: $-25^{\circ}\text{C} \sim +80^{\circ}\text{C}$

Order information
 RHTAY53-J09-XX M4

J09: C091 Miniature Circular Connector
 XX: Contacts Code
 M4: Soldering Connectors,
 Panel mount, Front lock, Female Pin

Female insert (mating side)	Contact code	Rated Current	Rated Voltage	Withstand voltage	Insulation resistance	Contact resistance	Contact Diameter
	02	7	250	1500	1500	5	$\phi 1.5$
	03	7	250	1500	1500	5	$\phi 1.5$
	04	7	250	1500	1500	5	$\phi 1.5$
	05	6	250	1500	1500	5	$\phi 1.5$
	5A	5	50	500	1000	5	$\phi 1.5$
	06	5	250	1500	1500	5	$\phi 1.5$
	07	5	50	800	1000	5	$\phi 1.5$
	08	5	50	500	1000	5	$\phi 1.5$
	12	5	50	500	1000	3	$\phi 1.0$
	14	5	50	500	1000	3	$\phi 1.0$
	16	5	50	500	1000	3	$\phi 1.0$
	19	5	50	500	1000	3	$\phi 1.0$
	24	5	50	500	1000	3	$\phi 0.5$
UNIT		A	V	V.AC	M Ω	M Ω	mm



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---	DRWN BY PAN
0~3	3~18	18~50	50~120
± 0.12	± 0.15	± 0.3	± 0.5

CHK'D BY FENG
APPR BY ZHAN

Soldering Connectors, Panel mount, Front lock, Female, C091 Miniature Circular
THIRD ANGLE PROJECTION
RHTAY53-J09-xxM4