



Panel mount



Front view



Back view

Material:
 SHELL Housing: Zinc alloy, Nickel plated
 Insert Housing: PA66+GF 20%
 Contact: Brass, Silver plated
 Termination: Solder
 Locking: Threaded Coupling
 Version: Straight
 Mating life: 500 cycles
 IP rating: IP65
 Cable Diameter: Ø6.0~Ø8.5mm
 Temperature Range: -25°C~+80°C

Order information
 RHTAY53-J09-XX M7

J09: C091 Miniature
 Circular Connector
 XX: Contacts Code
 M7: Soldering Connectors,
 Flange Panel mount, Female Pin

Female insert (mating side)	Contact code	Rated Current	Rated Voltage	Withstand voltage	Insulation resistance	Contact resistance	Contact Diameter
	02	7	250	1500	1500	5	Ø1.5
	03	7	250	1500	1500	5	Ø1.5
	04	7	250	1500	1500	5	Ø1.5
	05	6	250	1500	1500	5	Ø1.5
	5A	5	50	500	1000	5	Ø1.5
	06	5	250	1500	1500	5	Ø1.5
	07	5	50	800	1000	5	Ø1.5
	08	5	50	500	1000	5	Ø1.5
	12	5	50	500	1000	3	Ø1.0
	14	5	50	500	1000	3	Ø1.0
	16	5	50	500	1000	3	Ø1.0
	19	5	50	500	1000	3	Ø1.0
	24	5	50	500	1000	3	Ø0.5
UNIT		A	V	V.AC	MΩ	MΩ	mm