



Panel mount



Electrical & Mechanical data

IP rating:IP67

Contacts resistance:≤ 5 mΩ

Insulation resistance:≥100 MΩ

Orientation:Soldering, Rear lock,

Over mold/ Shell:Metal shell

Connector contacts:Brass with gold plated

Coupling nut/screw:Brass with nickel plated screw


Insert/ Housing: PA66+GF

Sealing:O-ring



Temperature Range:-25°C~+80°C



Front view



Back view



8P

Order information

RHT0Y12 A-CB1 XX

M12: Screw type

A: A-Coding

CB1:Soldering,Panel mount,

Rear lock,Female,CNC Screw

XX: Number of Contacts

No. of Pin	4 Pin	5 Pin	8 Pin
Rated current	4A	4A	2A
Rated voltage	250V	60V	30V



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm	SHEET SIZE: A4	SCALE:---
0~3	3~18	18~50
50~120		
±0.12	±0.15	±0.3
		±0.5


DRWN BY PAN

CHK'D BY FENG

APPR BY ZHAN

Soldering connector,Panel mount, Pear lock,
Automation technology, M12,Female,CNC Screw

THIRD ANGLE PROJECTION



RHT0Y12A-CB1XX