





	1	2	3	4	5	6	7	8	9
A									
B									
C									
D									
E									
F									
G	 NINGBO RHT ELECTRONIC CO.,LTD			UNITS:mm 0~3 3~18 18~50 50~120 ±0.12 ±0.15 ±0.3 ±0.5	SHEET SIZE: A4 SCALE: ---	DRWN BY PAN CHK'D BY FENG APPR BY ZHAN	Noise Cancelling mini microphone N6022 Serie THIRD ANGLE PROJECTION 		
	1	2	3	4	5	6	7	8	9



Unit:mm

Specifications:

Sensitivity:1KHz,0dB=1V/Pa;

-38±3dB;-40±3dB; -42±3dB; -44±3dB

Directivity:Noise Cancelling

Impedance:2.2KΩ Max.

Current consumption:0.5mA Max.

Operation voltage:1.0~10V


S/N ratio:60dB Min.

Sensitivity vs. Voltage:3dB Max. at VS=2.0V~1.5V


Std. Test Condition:94dB S.P.L @1KHz VS=2.0V

Frequency:20~16,000Hz

Frequency response



Schematic diagram VS=2V RL=2.2KΩ



ORDER INFORMATION

Product NO.: RHTCYN 6022 P - 423

Noise Cancelling mini microphone Serie

Dimensions

Note: Soldering: Pin Type Wire type

Sensitivity