






#### Specifications:

Sensitivity(1KHz,0dB=1V/Pa):

-34±3dB; -36±3dB; -38±3dB;

-40±3dB; -42±3dB; -44±3dB

Directivity:Noise Cancelling

Impedance:2.2KΩ Max.

Current consumption:0.5mA Max.

Operation voltage:1.0~10V


S/N ratio:60dB Min.

Sensitivity vs. Voltage:3dB Max. at VS=2.0V~1.5V


Std. Test Condition:94dB S.P.L @1KHz VS=2.0V

Frequency:20~16,000Hz

Frequency response



Schematic diagram VS=2V RL=2.2KΩ



#### ORDER INFORMATION

Product NO.: RHTCYN 9750 P - 423

Noise Cancelling mini microphone Serie

Dimensions

Note: Soldering: PiPin Type W:Wire type

Sensitivity



NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

Noise Cancelling mini microphone N9750 Serie

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTCYN9750P-423