



Specification For Approval

Customer Name : _____

RHT P/N: _____ RHTCYPB-23x10

Description : _____

Date : _____ 2026-7-21

Approved by
Sign : date :
Please return by one copy

Design: _____ Pan _____ Checked: _____ Andy _____ Approved: _____ Feng _____

Address:Maoshan Industrial Park, Huajiafen Village, Jiangshan Town,
Yinzhou District Ningbo City, Zhejiang,POSTAL:315193
Tel:086-574-56176016 M:0086-15168501684
E-mail:info@rhatecp.com Web:www.rhatecp.com www.rhtconn.com


A. SCOPE

This specification applies Internally driven piezo buzzer,with wire. RHTCYPB-23x10

SPECIFICATION

No.	Item	Unit	Specification	Condition
1	Oscillation Frequency	KHz	3.5±0.5	
2	Operating Voltage	VDC	3 ~ 24	
3	Rated Voltage	VDC	12	
4	Current Consumption	mA	MAX. 10	at Rated Voltage
5	Sound Pressure Level	dB	MIN. 85	at 10cm at Rated Voltage
6	Tone Nature		Constant	
7	Operating Temperature	°C	-40~ +85	
8	Storage Temperature	°C	-40 ~ +105	
9	Dimension	mm	Φ 24.0 x H10	See appearance drawing
10	Weight (MAX)	gram	3.5	
11	Housing Material		ABS(Black)	
12	Leading Pin		Wire Type	See appearance drawing
13	Environmental Protection Regulation		RoHS	

B. APPEARANCE DRAWING



Tol: ±0.5

Unit: mm


D. TESTING METHOD

Standard Measurement conditions


Temperature: $25 \pm 2^\circ\text{C}$ Humidity: 45-65%

Acoustic Characteristics:



The oscillation frequency, current consumption and sound pressure are measured by the measuring instruments shown below




In the measuring test, buzzer is placed as follows:



E. VOLTAGE / CURRENT / SOUND PRESSURE CHARACTERISTICS



F. RELIABILITY TEST

NO.	ITEM	TEST CONDITION AND REQUIREMENT
1	High Temperature Test (Storage)	After being placed in a chamber with 70 $\pm$ 2 $^{\circ}$ C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: $\pm$ 10dB.
2	Low Temperature Test (Storage)	After being Placed in a chamber with -30 $\pm$ 2 $^{\circ}$ C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: $\pm$ 10dB.
3	Humidity Test	After being Placed in a chamber with 90-95% R.H. at 40 $\pm$ 2 $^{\circ}$ C for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: $\pm$ 10dB.
4	Temperature Cycle Test	The part shall be subjected to 5 cycles. One cycle shall be consist of:  Allowable variation of SPL after test: $\pm$10dB.
5	Drop Test	Drop on a hard wood board of 4cm thick, any directions ,6 times, at the height of 75cm. Allowable variation of SPL after test: $\pm$ 10dB.
6	Vibration Test	After being applied vibration of amplitude of 1.5mm with 10 to 55 Hz band of vibration frequency to each of 3 perpendicular directions for 2 hours . Allowable variation of SPL after test: $\pm$ 10dB.
7	Solderability Test	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of +300 $\pm$ 5 $^{\circ}$ C for 3 $\pm$ 1 seconds . 90% min. lead terminals shall be wet with solder (Except the edge of terminals).
8	Terminal Strength Pulling Test	The force of 9.8N(1.0kg) is applied to each terminal in axial direction for 10 seconds. No visible damage and cutting off.

TEST CONDITION.

Standard Test Condition	:	a) Temperature: +5 ~ +35 $^{\circ}$ C	b) Humidity : 45-85%	c) Pressure : 860-1060mbar
Judgment Test Condition	:	a) Temperature : +25 $\pm$ 2 $^{\circ}$ C	b) Humidity : 60-70%	c) Pressure : 860-1060mbar

G. PACKING STANDARD

Each minimum package unit of products shall be in a carton box and it shall be clearly marked with Part Number, quantity and outgoing inspection number. There shall be no mechanical damage on products during transportation and/or in storage.