



Characteristics:

Voltage Rating: 58V DC

Current Rating: 2A~30A

Operating Temperature: -40°C to +125°C

Material:

Body: PC, UL94-V2

Contact: Zinc Alloy

Time-Current Characteristics

% of Rating	Opening Time
110	>360,000s
135	0.75 to 1800s
200	0.15 to 5s
350	0.04 to 0.5s
600	0.02 to 0.1s

Part Number	Current Rating	Housing Color
RHTDY-269B-002-A	2A	Grey
RHTDY-269B-003-A	3A	Violet
RHTDY-269B-004-A	4A	Pink
RHTDY-269B-005-A	5A	Orange
RHTDY-269B-008-A	7.5A	Brown
RHTDY-269B-010-A	10A	Red
RHTDY-269B-015-A	15A	Blue
RHTDY-269B-020-A	20A	Yellow
RHTDY-269B-025-A	25A	Natural
RHTDY-269B-030-A	30A	Green

RHTECP NINGBO RHT ELECTRONIC CO.,LTD

UNITS:mm

SHEET SIZE: A4

SCALE:---

DRWN BY PAN

58V Low Profile Miniature Blade Fuse

0~3

3~18

18~50

50~120

CHK'D BY FENG

THIRD ANGLE PROJECTION

±0.12

±0.15

±0.3

±0.5

APPR BY ZHAN



RHTDY-269B-XX-A